

# Viniles de transferencia térmica Siser

## Guía de valores y ajustes de corte Graphtec CE

**GRAPHTEC**



**Siser**®

**GRAPHTEC**

	<i>EasyWeed®</i>	<i>Easyweed® Foil</i>	<i>EasyWeed® Electric</i>	<i>EasyWeed® Stretch</i>	<i>Easyreflective™</i>	<i>Easyweed® Extra</i>	<i>Easyweed® SubBlock</i>	<i>EasyPatterns™</i>
<b>Blade:</b>	45 grados	45 grados	45 grados	45 grados	45 grados	45 grados	45 grados	45 grados
<b>Pressure:</b>	8-9	8-9	8-9	9-10	11	8-9	8-9	8-9
<b>Tool:</b>	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O
<b>Speed:</b>	30 cm/s	30 cm/s	30 cm/s	30 cm/s	30 cm/s	30 cm/s	30 cm/s	30 cm/s

**GRAPHTEC**

	<i>EasyWeed® Adhesive</i>	<i>Metal</i>	<i>Glitter</i>	<i>Holographic</i>	<i>StripFlock PRO®</i>	<i>Brick™600</i>	<i>Blackboard™</i>	<i>EasySubl™</i>
<b>Blade:</b>	45 grados	45 grados	45 grados	45 grados	45 grados	60 grados	45 grados	45 grados
<b>Pressure:</b>	6-7	17-18	17-18	17-18	10	11-12	7-8	10-12
<b>Offset:</b>	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O	CBO9U+O
<b>Speed:</b>	30 cm/s	30 cm/s	30 cm/s	30 cm/s	30 cm/s	25 cm/s	50 cm/s	30 cm/s